

Challenge in beam instrumentation and diagnostics

T. Lefevre – CERN


Outline

- Main challenges of Beam Instrumentation
- Snapshot of R&D activities and key technologies
- Conclusions




Challenge for Beam instrumentation at CERN – today and tomorrow

- Maintaining a large (>10000 instruments)
 and diverse Beam instrumentation system
- Dealing with larger beam intensities in the accelerator complex
- Still a need for consolidation (towards more reliability and efficiency) and improved performance (some missing diag, e.g. beam halo)





Looking forward ... Bigger, Faster, Better!




https://clic.cern/




https://fcc.web.cern.ch/Pages/default.aspx

Shorter electron bunches, lower emittance / beam size, very large number of instruments, ...



https://pbc.web.cern.ch/





https://muoncollider.web.cern.ch/welcome-page-muon-collider-website

Higher beam intensities on target, ..



Launch a bottom-up R&D survey

- Identify state-of-the-art technologies and future trends in our field
- Collect 'all' requirements from Projects and future Studies



- Build a medium to longer term plan of R&D roadmap to foster our expertise and maintain top performance
- Identify possible future collaborations synergies (Group, CCTB)
- Align our Roadmap to the CERN Priorities
 - Future students / Graduates needs



Launch a bottom-up R&D survey

	R&D	Challenges	Key Technologies	Status	Funded by	Past achievements (Tests, Publications,)	Useful for				
F							CERN Machines	CERN Projects	CERN Studies	Accelerators outside CERN	Knowledge transfer

Potential quantities	External collaborators	CERN Group involved	SY-BI section and contact persons		



Main challenges in Beam instrumentation

- Dealing with higher beam power
 - Low-impedance design require for all instruments to limit heating problems
 - Higher beam densities putting strong limitations of interceptive diagnostics (screen, wire)
 - Need for robust and reliable machine protection systems
 - Measuring beam quality, tail and halo particles
- Measuring and conserving small beam emittance and small beam size
 - Unprecedented request for higher spatial resolution for position (nanometer) and transverse profile (micrometer) monitors
- Measuring the ultra-short
 - Sub-ps bunches and fast beam instabilities
- Measuring the ultra-low and DC beams
 - Slowly extracted beams and exotic beams, i.e. AD/ELENA and Isolde/REX
- Exposed to higher radiation environement
 - Rad-hard / Rad-tol design
- Treatment of increasingly more data bunch-bunch everything!
- Cost effective solution for large systems (BPM and BLM)




On-going R&D in the BI group

- Pushing the state-of-the-art in interceptive diagnostics
- Non-invasive beam size monitors
- 'New' techniques for short bunches
- Innovative design of Electromagnetic pick-ups
- Techniques for low beam intensity and DC beams
- Robust particle detectors as BLM
- State-of-the-art electronic development



State-of-the-art Interceptive beam diagnostics

Towards a modern optimised design of SEM grids



Improved UHV cabling and connectors...

From kapton wiring to Flex cables and connectors













State-of-the-art Interceptive beam diagnostics


20m/s rotational Wire Scanner (LIU project)



Monitors also produced for ESS










State-of-the-art Interceptive beam diagnostics - Screens

High resolution beam size monitor using **Optical Transition Radiation** Point Spread Function (PSF) with KEK and RHUL





600nm beam size measured @ ATF2-KEK in VUV range funded by CLIC – stopped now



State-of-the-art Interceptive beam diagnostics - Screens

Imaging system for high intensity beams using Optical Transition Radiation



SiC 0.5mm 0.1mm

 $Al_2O_3:CrO_2$ 0.5mm

LHC Dump line

Sigradur G Glassy C 0.5mm

288 bunches at 1E11 with $\sigma_H = 0.26$ mm and $\sigma_V = 0.28$ mm ligh-Radiation to Material S. Burger et al, IBIC 2016

Surface homogeneity/flatness/roughness, high reflectivity




CNGS

State-of-the-art Interceptive beam diagnostics - Screens

Replacing the best thermally resistant material (carbon wire and glassy Carbon) by low density materials (CNNT wire and graphene foil)

On-going studies with students (Southampton Uni. and Malta uni.) and Workshop in 2023 https://indico.cern.ch/event/1275649/







Non-invasive beam size monitors

- Laser-based Techniques
- Gas-based Techniques
- Polarisation radiation Techniques
- Synchrotron radiation Techniques



Non-invasive beam size monitors – laser-based





Demonstrated 1 µm measurement resolution


15 years on R&D on ATF2 ring and extraction line with RHUL, KEK

H. Sakai et al, Physical Review ST AB 4 (2001) 022801 & ST AB 6 (2003) 092802

S. T. Boogert et al., PRSTAB 13, 122801 (2010)


L. Corner et al., IPAC, Kyoto, Japan (2010) pp3227

Funded by LC/CLIC → now FCC Polarimeter and transverse beam size (IJCLab)







Non-invasive beam size monitors – laser-based



<u>Laser based - Emittance-meter</u>



In-vacuum pixel Diamond sensor



T. Hofmann et al., NIMA 830 (2016) 526 T. Hofmann et al., NIMA 903 (2018) 140

Collab. with RHUL – stopped now


Works only for H- beams




Non-invasive beam size monitors – gas-based

Gas ionization monitor using hybrid pixel detector

S. Levasseur et al., Journal of Instrumentation, 12 C02050 (2017)



Hor. beam size/position evolution during 1.2s long cycle @ PS




From PS to SPS and LHC, possibly TLs and medical machine From Timepix 3 to Timepix4



Non-invasive beam size monitors – gas-based


Imaging system using fluorescence of supersonic **gas** curtain with Uni. Liverpool and GSI





Non-invasive beam size monitors via polarization radiation

Diffraction radiation from high precision slits with KEK and RHUL







Non-invasive beam size monitors via polarization radiation


Diffraction Cherenkov radiation imaging system with RHUL, KEK & Cornell Uni.

mm hor. beam size @ CESRTA



R.Kieffer et al., PRL **121** 054802 (2018) R.Kieffer et al., PRAB **23** 042803 (2020)





hor. beam size @ ATF2-KEK


1.2GeV electrons



Dielectric ($\varepsilon(\omega)$, $\sigma(\omega)$)

Particle (β,γ)


Non-invasive beam size monitors via synchrotron radiation






Non-invasive beam size monitors via synchrotron radiation

X-ray interferometry using near field speckles with Uni. Milano and Alba





M. Siano et al., PRAB 25 052801 (2022)

The probe: silica (SiO₂) spheres, 500 nm, in water



Non-invasive beam size monitors

Laser-based Techniques
 LC / CLIC and L4

FCC-ee

Gas-based Techniques

Proton Synchrotrons

HL, FCC-hh, TLs, ...

Polarisation radiation Techniques
 LC / CLIC


HL, FCC-ee, FCC-hh, MuColl

• Synchrotron radiation Techniques

HL, FCC-ee, FCC-hh, MuColl



High dynamic range measurements for Beam halo monitoring






Longitudinal phase space reconstruction

Kalman filter

D. Alves et al., PRAB 24 (2021) 072801




Towards an on-line longitudinal phase space measurements – LHC and others circulation machine



Longitudinal profile of short bunches


Streak Camera @ CTF3

- Simple but expensive
- Cannot do bunch by bunch measurements



C.P. Welsch et al., Journal of Instrumentation 1 P09002 (2006)


A.E.Dabrowski et al., Journal of Instrumentation 7 P01005 (2012)








Longitudinal profile of short bunches

Electro-optical sampling for sub-ps/ps time domain measurement












Initiated through CLIC study → FCC study for bunch-by bunch measurement by KIT




High bandwidth BPM for HL using electro-optical pick-up with RHUL








450GeV protons @ HIRADMAT



200MeV, ps long electron bunch @ CLEAR







Longitudinal profile of short bunches

Bunch spectrum measurement using Coherent Cherenkov Diffraction Radiation








Bandwidth > 1GHz designed for LHC/SPS

A. Curcio et al, PRAB **23** 022802 (2020) A. Curcio et al, Phys Letters A **391** 127235 (2021)





High frequencies BPM using dielectric pick-up with RHUL



Paper submitted to PRX in Aug. 2023


For electrons @ aWAKE in presence of Protons









High directivity cryogenic stripline BPM for HL-LHC












LHC Collimator BPMs


- Allow the centering and adjustment of each collimator aperture in few minutes
- Allow constant measurements and generate interlock in case of dangerous position drifts






- Should be compatible with UHV conditions and 250C bake-out
- Should withstand high radiation dose (~20 MGy TID)
- Should reach and position accuracy better than 20um with micron resolution






LHC Collimator BPMs


Electrostatic Buttons





• SiO2 cables to route the cable outside of vacuum rad-hard, outgassing rate <1e-9 mbar· l/s








BPMs in jaws become a standard for collimation



High sensitivity Schottky monitoring – DC and Short bunches

Long history of CERN contributions in shot noise, schottky signals and stochastic cooling



<u>LHC – high intensities bunches</u>

K. Lasocha et al, PRAB 23 (2020) 062903

K. Lasocha et al, PRAB 25 (2022) 062801


Collab. with ABP, N. Mounet and C. Lannoy Ph.D



Beam position for DC beams using shot noise – O. Marqversen, M. Gasior and D. Alves https://indico.cern.ch/event/1220800/



DC beam monitoring – beam position using EO crystal






Secondary beams from fixed target

The Past

- Scintillator paddles
- Multi-Wire Proportional Chambers (MWPC)
- Delay Wire Chambers (DWC)
- Filament Scintillators (FISC)




Today ... The Future

Scintillating fibers array

- Plastic fiber (not rad-hard)
- Gas/liquid filled capillary tube

Cherenkov optical fibers array







Hollow core fiber



Particle detectors for Beam Loss Monitoring

High sensitvity **lonisation chamber**






Monitors also produced for ESS and FRIB




Particle detectors for Beam Loss Monitoring

Semiconductor as fast BLM



- Diamond sensor today
- Timepix-based BLM under study









Particle detectors for Beam Loss Monitoring

Capture angle

Cherenkov in optical fiber as continuous BLM







Dependence with fibre distance

Upstream - SiPM3010
Downstream - SiPM3015
Thick target (2 cm)

y = 0.0060x² -0.6959x + 26.8176
r² = 0.979

y = -0.0000x² -0.0188x + 2.6784
r² = 0.828

0 25 30 35 40 45 50 55
Fiber Position (cm)


Paper submitted to PRAB in sep 2023

CLIC → NACONS → FCCee



R&D on Imaging system using Machine learning

An image will not be preserved at the exit of one fiber Can it be recovered?




Applying Machine learning algorithms to beam imaging technology


G. Trad et al, IPAC 2022 pp39



High resolution measurements for tune and collimator BPM based on diode detection

Diode ORbit and Oscillation electronic (DOROS)





Resolution measured at 100nm for BPM, ~10nm for tune monitors – FCup AWARD to Marek Gasior




Rad-tol / Rad-hard Front-Ends with EP-ESE



ADC board

C-GEFE carrier board with FPGA

L-GEFE GTBx board with VTRx



2x 200 MHz hairpin band-pass filter

output amplifiers & anti-aliasing LPFs

calibration (CAL) signal processing

logarithmic amplifiers Analog Devices ADL5519

17 dB couplers for MID & LO channels


6 dB couplers for the CAL signal






M. Barros marin et al, Journal of Instrumentation, vol.11 C02062 (2016)

HL BLM ASIC performance – 10⁹ dynamic range









Standardising read-out platform – performed via LIU project




- Wire scanners for all machines
- Fast BCTs for all machines (if included future consolidation for PS complex)
- BLM for all machines
- BPM for SPS and PS-to-SPS TLs
- LHC luminosity monitors

New platform for HL/CONS based on SoM


A. Boccardi et al, Journal of Instrumentation, vol.8 C03006 (2013)



RF System-on-Chip as fast DAQ in the multi GSa/s – developed for HL IP BPMs




IPAC presentation - Paper in prepapration



New platform for HL/CONS based on SoM




Electro-optical time-stretch acquisition system with >40GHz and >100GSa/s





Poster at IBIC 2023



A SNAPSHOT OF CERN BEAM INSTRUMENTATION R&D ACTIVITIES

T. Lefevre*, A. Boccardi, S. Jackson, D. Louro Alves, F. Roncarolo J. Storey, R. Veness, C. Zamantzas CERN, Geneva, Switzerland

Abstract

The CERN accelerator complex stands out as unique scientific tool, distinguished by its scale and remarkable diversity. Its capacity to explore a vast range of beam parameters is truly unparalleled, spanning from the minute energies of around a few keV and microampere antiproton beams, decelerated within the CERN antimatter factory, to the 6.8 TeV high-intensity proton beams that race through the Large Hadron Collider (LHC). The Super Proton Synchrotron (SPS) ring plays also a crucial role by slowly extracting protons at 400 GeV. These proton currents are then directed toward various targets, generating all sorts of secondary particle beams. These beams, in turn, become the foundation of a diverse fixed-target research program, enabling scientific exploration across a wide spectrum. Moreover, as CERN looks ahead to future studies involving electron-positron colliders, the development of cutting-edge diagnostics for low emittance and short electron pulses is also underway. This contribution serves as a snapshot, shedding light on the main R&D initiatives currently underway at CERN in the field of beam instrumentation.

INTRODUCTION

The CERN accelerator complex is a dynamic and continually evolving system. Over a decade ago, an ambitious global initiative was launched to enhance the collision capabilities of the Large Hadron Collider (LHC). This initiative aims to achieve higher collision rates and is executed in phases. The initial phase focused on the LHC highertor Ugrade program [1], which successfully generated higher brightness beams within the CERN injector complex. Building on this achievement, the subsequent stage of the high Luminosity LHC upgrade (HL-LHC) [2] is scheduled for implementation from 2026 to 2028. This phase aims to further elevate beam intensities and reduce emittance, introducing novel challenges to beam instrumentation. These instruments must adapt to unprecedented beam densities while maintaining the highest reliability and precision.

Beyond its contributions to the LHC and its physics endeavors, CERN has embarked on a comprehensive consolidation of the fixed target physics program in the 'North Area' of the Super Proton Synchrotron (SPS). This undertaking necessitates a complete overhaul of the instrumentation employed for extracting continuous beams from the SPS. These beams are subsequently directed towards various targets and experimental zones.

Anticipating the completion of the LHC's scientific program, the scientific community's aspirations encompass the exploration of $e^- - e^+$ collisions at up to 380 GeV center of mass energies. While the Compact Linear Collider (CLIC) [3] has been under scrutiny for decades. CERN is currently engaged in assessing the feasibility of the 91-kilometer-long Future Circular Collider (FCC). The FCC would initially focus on lepton collisions [4] and potentially accommodate 100 TeV proton collisions in subsequent phases, using the same infrastructure. Although linear and circular colliders differ in their design and implementation, there are notable similarities in terms of beam properties, beam energy, intensity, transverse and longitudinal sizes, as well as the demand for a high level of radiation tolerance within the tunnel. This suggests the prospect of adapting technologies initially developed for CLIC for use in the FC-Cee.

In this paper, we provide a comprehensive overview of the ongoing R&D endeavors at CERN in the realm of beam instrumentation. This encompasses a spectrum of activities, including the design of innovative electromagnetic pick-ups, the refinement of techniques for measuring transverse profiles of high power density beams, advancements in short longitudinal beam profiling, the optimisation of high dynamic range particle detectors and the latest strides in read-out electronics and digital acquisition systems. By shedding light on these R&D activities, we aim to present the essence of CERN's pursuit of cutting-edge instrumentation techniques.

COMPLEX DESIGN OF ELECTROMAGNETIC PICK-UPS

Within the scope of the HL-LHC program, the demand for large-aperture, high-field quadrupole magnets has surged to compress proton beam sizes during collisions to unprecedentedly minuscule dimensions. This new configuration requires novel cryogenic directional stripline beam position monitors [5], enabling the measurement of counterpropagating beams with a precision surpassing a mere micron. This intricate design encompasses Tungsten alloy inserts, strategically positioned to absorb collision debris and curtail radiation doses to neighboring magnets. Furthermore, these monitors are coated with copper and NEG (Non-Evaporable Getter) coatings, a dual-layer approach that minimizes beam impedance and paves the way for attaining ultra-nieth vacuum conditions.

Amid recent advancements, beam position monitors (BPMs) with heightened frequency bandwidth have garnered substantial interest. This is not only pertinent to short electron bunches but also to furnish intrabunch monitoring with fast time response for high-intensity proton beams. A range of technologies is presently under exploration, featuring



^{*} thibaut.lefevre@cern.ch

Next Steps

- Provide an Overview of the previous BI R&D achievements
- Provide a Roadmap of BI future R&D activities
 - By Technology
 - By Project
- Provide an updated list of future opportunities
 - For Collaboration
 - For Students (TS and Ph.D) and Graduates



Thanks for your attention



